

カ ン タ ン

ラ ク 4 ン

ア シ ス ト



JAPAN QUALITY

Power-Assisted Lift Table Truck

プッシュ
キャデ
プッシュキャデ

Powerfully assists
daily transportation work
with originally developed
sensing technology.

FOUNDED 1934



OKUDAYA GIKEN CO., LTD.
OSAKA JAPAN

ESTABLISHED 1954

PUSH CADDIE プッシュキャデ

The operation is the same as daily operation.
Powerfully assists daily transportation work
with originally developed sensing technology.

PUSH CADDIE provides a comfortable workplace especially for women and elderly workers.

There is the voice guidance in Japanese, English and Chinese language.

※ It can not be changed after purchasing the product

『Power-Assisted system』 can be installed on the existing manual lift table CADDIE.

※ Available for LT-H250-8 and LT-H250-8S

『Battery pack』 『AC adapter』 『Battery charger』 can be added as options.



Grip the handle to activate the power assist function



The high efficiency motor can be energy-saving and powerfully assisted



Simple and functional operation panel with the voice guidance



Re-chargeable Lithium-ion battery



The spare battery and stationary charger can save charging time

※ Spare battery sold separately

Specifications of PUSH CADDIE


Lifting / Lowering function is manual.

Specification Model	Maximum Capacity	Min. H (mm)	Max. H (mm)	Table Size (mm) Length x Width	Overall length (mm)	Overall Width (mm)	Overall Height (mm)	Steering wheel Dia. φ x Width (mm)	Drive wheel Dia. φ x Width (mm)	Battery (Lithium-ion battery)	Number of lifting time	Net weight (kg)
	(kg)	A	B	C x D	E	F	G					
LTX- AS250- 8S	250	245	850	800 x 500	1,055	500	895	Rubber 100 x 32	Urethane 125 x 27	14.4V-2.5Ah	24	68
LTX- AS250- 8											24 (12)	68

※ Automatic Battery Charger (AC 100-240V single phase)

※ Lifting times in () are quick-lifting times on the condition that no loads are imposed.

■ Dimensions



Specifications of POWER-ASSISTED SYSTEM

Specification Model	Maximum capacity (kg)	Maximum movement speed (km / h)	Breaking	Drive wheel Dia. φ x Width (mm)	Battery (Lithium-ion battery)	Battery charger (Adapter type)	Total weight (kg)
AS-250	250	3.0 ~ 4.2	Electro-magnetic brake	125 x 27	14.4V-2.5Ah	AC100V ~ 240V	12

※ Above system includes Battery pack, AC adapter, Battery charger. (One for each)

Created by Highly Experienced Hydraulic Equipment Makers.

Originality Produces Know-how



OKUDAYA GIKEN CO., LTD.

263 Tanjo, Mihara-ku, Sakai-city, Osaka 587-0011, JAPAN.
TEL 81-723-61-7861 FAX 81-723-62-2102

URL : <http://www.opk.co.jp>



As of December 2023

All rights reserved.

* Products with special specifications besides those with standard specifications are manufactured as well. Feel free to contact OKUDAYA GIKEN.
The specifications described in this catalog are subject to change without notice for product improvement.
* The colors of actual products may be more or less different from those printed in this catalog.