

Global Low Lift Pallet Truck



GB



Global collaborate with OPK group companies realized significant cost reduction.

## olobal Netwo

## "Low Cost" and "High Quality"! Remarkable Cost Performance is Realized!

- ◆ Reliable "Made in Japan" product with good after-sales services
- ◆ Reasonable price realized by global collaborate with OPK group companies
- ◆ Simple mechanical sturucture for easy maintenance
- ◆ Smooth running by variable speed controlled DC motor
- ◆ New designed bumper for compact body
- ◆ Minimum turning radius: 1620mm
- ◆ Emergency shutoff system is equipped
- ◆ Customization is available

(Please ask our agent/distributor near you for more information)



Stationary Battery Charger



Operating Handle

Global Low Lift Pallet Truck GBL-20S



Minimum Turning Radius: 1620mm

Bumper

## Global Low Lift Pallet Truck

\*The specifications are subject to change without prior notice.

ľ	Specifications Capacity		Min. H	Max. H	Fork			Overall	Overall Overall		Drive Speed (km/h)		Drive Wheel Load Whe	Load Wheel		Net	1
					Length	Outer Width	Inner Width	Length	Width	Height [Automatic Speed Reduction]		Dia.φ×Width	Dia.φ×Width	Battery	Weight	1	
	Model	(kg)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	Unloaded	Loaded	(mm)	(mm)		(kg)	
	GBL-20S	2000	80	200	1070	580	280	1720	580	1200	0 ~ 4.5	0 ~ 4.0	Urethane	Urethane	DC12V	230	]
													250×80	80×73	50AH/5HR×2		

<sup>\* &</sup>quot;Drive Speed" shown above are at "POWER MODE".

Drive speed at "ECONOMY MODE" are half of them.

\*Please contact our agent/distributor near you for more information.



Cycle Times: Approx. 70times (70% discharge)

<sup>\* 1</sup> cycle time: 10m running with load and 10m running with no load (full charged new battery)

<sup>\*</sup> Automatic Stationary Battery Charger (100~240V single phase)