



LT-F Series



- 2.0 t · 3.0 t New Lineup
- Options Bellows-type Cover
 Pushbutton Switch



■ Specifications of Lift Table COTEE <LT-F Type>

Specifications	Capacity	Min. H	Max. H	Table Size (mm)		Power	Lifting Time	Operation	Net Weight
Model	(kg)	(mm)	(mm)	Width	Length	Source	(60/50Hz)		(kg)
LT-F200-0712	2,000	180	1,000	700	1,200	AC 200V	36/44	Foot Switch	250
LT-F200-0716	2,000	205	1,120	700	1,620	AC 200V	46/56	Foot Switch	355
LT-F200-1020	2,000	215	1,465	1,000	2,000	AC 200V	39/46	Foot Switch	490
LT-F300-0716	3,000	220	1,135	700	1,620	AC 200V	64/77	Foot Switch	450
LT-F300-1020	3,000	270	1,520	1,000	2,000	AC 200V	59/70	Foot Switch	690

* Different voltage available as option.

LT-S Series

AC100V, same as household power source Originally developed power cylinder for steady up and down

Automatic control of downward speed depend on the load weight (with in the capacity range) Microcomputer on-boarded

Quick dropping protecting function

Bellows-type cover equipped model for safety and dust prevention



LT -S10-0407

LT-E Series

Wide variety of models for various purposes and uses Originally developed hydraulic lifting mechanism for smooth up and down Mounted type easily combined with assembly and process lines Pushbutton switch for easy operation, Foot Switch available as option



LT -E25-0508